


[FORT] Práctica 5: Control de Acceso a nivel de aplicación


1. Habilita los servicios FTP en MAQUINA1 ejecutando `/usr/sbin/ftpd -D`



```
Terminal
File Edit View Search Terminal Help
root@fso2025:~# /usr/sbin/ftpd -D
root@fso2025:~#
```

2. Revisa las conexiones ftp y ssh de MAQUINA2 a MAQUINA1 usando las direcciones de red locales

Comprobación de SSH:



```
Terminal
File Edit View Search Terminal Help
root@fso2025:~# ssh 192.168.2.10
The authenticity of host '192.168.2.10 (192.168.2.10)' can't be established.
ED25519 key fingerprint is SHA256:Lmnh/hNAcl9oSvUiANw6AwXDYBHVf+1LP7MpuoAyCc4.
This host key is known by the following other names/addresses:
  ~/.ssh/known_hosts:1: [hashed name]
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '192.168.2.10' (ED25519) to the list of known hosts.
root@192.168.2.10's password:
```

```
Terminal
File Edit View Search Terminal Help
root@fso2025:~# ssh 192.168.3.10
The authenticity of host '192.168.3.10 (192.168.3.10)' can't be established.
ED25519 key fingerprint is SHA256:Lmnh/hNAcl9oSvUiANw6AwXDYBHVf+1LP7MpuoAyCc4.
This host key is known by the following other names/addresses:
  ~/.ssh/known_hosts:1: [hashed name]
  ~/.ssh/known_hosts:4: [hashed name]
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '192.168.3.10' (ED25519) to the list of known hosts.
root@192.168.3.10's password:


root@fso2025:~# ssh 192.168.4.10
The authenticity of host '192.168.4.10 (192.168.4.10)' can't be established.
ED25519 key fingerprint is SHA256:Lmnh/hNAcl9oSvUiANw6AwXDYBHVf+1LP7MpuoAyCc4.
This host key is known by the following other names/addresses:
  ~/.ssh/known_hosts:1: [hashed name]
  ~/.ssh/known_hosts:4: [hashed name]
  ~/.ssh/known_hosts:5: [hashed name]
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '192.168.4.10' (ED25519) to the list of known hosts.
root@192.168.4.10's password:

root@fso2025:~# ssh 192.168.12.10
The authenticity of host '192.168.12.10 (192.168.12.10)' can't be established.
ED25519 key fingerprint is SHA256:Lmnh/hNAcl9oSvUiANw6AwXDYBHVf+1LP7MpuoAyCc4.
This host key is known by the following other names/addresses:
  ~/.ssh/known_hosts:1: [hashed name]
  ~/.ssh/known_hosts:4: [hashed name]
  ~/.ssh/known_hosts:5: [hashed name]
  ~/.ssh/known_hosts:6: [hashed name]
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '192.168.12.10' (ED25519) to the list of known hosts.
root@192.168.12.10's password:

root@fso2025:~# ssh 192.168.13.10
The authenticity of host '192.168.13.10 (192.168.13.10)' can't be established.
ED25519 key fingerprint is SHA256:Lmnh/hNAcl9oSvUiANw6AwXDYBHVf+1LP7MpuoAyCc4.
This host key is known by the following other names/addresses:
  ~/.ssh/known_hosts:1: [hashed name]
  ~/.ssh/known_hosts:4: [hashed name]
  ~/.ssh/known_hosts:5: [hashed name]
  ~/.ssh/known_hosts:6: [hashed name]
  ~/.ssh/known_hosts:7: [hashed name]
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '192.168.13.10' (ED25519) to the list of known hosts.
root@192.168.13.10's password: █
```

```
root@fso2025:~# ssh 192.168.14.10
The authenticity of host '192.168.14.10 (192.168.14.10)' can't be established.
ED25519 key fingerprint is SHA256:Lmnh/hNAcl9oSvUiANw6AwXDYBHVf+1LP7MpuaAyCc4.
This host key is known by the following other names/addresses:
  ~/.ssh/known_hosts:1: [hashed name]
  ~/.ssh/known_hosts:4: [hashed name]
  ~/.ssh/known_hosts:5: [hashed name]
  ~/.ssh/known_hosts:6: [hashed name]
  ~/.ssh/known_hosts:7: [hashed name]
  ~/.ssh/known_hosts:8: [hashed name]
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '192.168.14.10' (ED25519) to the list of known hosts.
root@192.168.14.10's password: █
```

Comprobación ftp



```
Terminal
File Edit View Search Terminal Help
root@fso2025:~# ftp
ftp ftpd
root@fso2025:~# ftp 192.168.2.10
Connected to 192.168.2.10.
220 fso2025.nowhere.org FTP server (GNU inetutils 2.4) ready.
Name (192.168.2.10:root):

root@fso2025:~# ftp 192.168.3.10
Connected to 192.168.3.10.
220 fso2025.nowhere.org FTP server (GNU inetutils 2.4) ready.
Name (192.168.3.10:root):

Terminal
File Edit View Search Terminal Help
root@fso2025:~# ftp 192.168.4.10
Connected to 192.168.4.10.
220 fso2025.nowhere.org FTP server (GNU inetutils 2.4) ready.
Name (192.168.4.10:root):

root@fso2025:~# ftp 192.168.12.10
Connected to 192.168.12.10.
220 fso2025.nowhere.org FTP server (GNU inetutils 2.4) ready.
Name (192.168.12.10:root):
```

```
root@fso2025:~# ftp 192.168.13.10
Connected to 192.168.13.10.
220 fso2025.nowhere.org FTP server (GNU inetutils 2.4) ready.
Name (192.168.13.10:root):

root@fso2025:~# ftp 192.168.14.10
Connected to 192.168.14.10.
220 fso2025.nowhere.org FTP server (GNU inetutils 2.4) ready.
Name (192.168.14.10:root):
```

3. Configura rcppwrappers (/etc/hosts.allow y /etc/hosts.deny) en MAQUINA1 para:

Aceptar todas las conexiones ftp excepto las que vienen de


- 192.168.2.X
- 192.168.3.X
- 192.168.4.X

Rechazar todas las conexiones ssh que vienen de:

- 192.168.12.x
- 192,168.13.x
- 192.168.14.X


Comenzamos editando el archivo /etc/hosts.allow para aceptar todas las conexiones menos las indicadas con las siguientes líneas:

```
vsftpd: ALL #Se permite todo el tráfico FTP
vsftpd: !192.168.2.0/24, !192.168.3.0/24, !192.168.4.0/24 #Se bloquean los rangos indicados para conexiones FTP
```




Tras eso procedemos a editar el archivo /etc/hosts.deny para bloquear las conexiones indicadas con las siguientes líneas:

sshd: 192.168.12.0/24, 192.168.13.0/24, 192.168.14.0/24 #Se bloquea el SSH para las direcciones indicadas



4. Revisa las conexiones ftp y ssh desde MAQUINA2 a MAQUINA1

Comenzamos revisando las conexiones FTP:




```
Terminal
File Edit View Search Terminal Help
root@fso2025:~# ftp 192.168.2.10
ftp: Can't connect to `192.168.2.10:21': Connection refused
ftp: Can't connect to `192.168.2.10:ftp'
ftp> exit
root@fso2025:~# ftp 192.168.3.10
ftp: Can't connect to `192.168.3.10:21': Connection refused
ftp: Can't connect to `192.168.3.10:ftp'
ftp>
ftp> exit
root@fso2025:~# ftp 192.168.4.10
ftp: Can't connect to `192.168.4.10:21': Connection refused
ftp: Can't connect to `192.168.4.10:ftp'
ftp> exit
```

Tras eso revisamos las conexiones ssh:

```
Terminal
File Edit View Search Terminal Help
root@fso2025:~# ssh 192.168.2.10
root@192.168.2.10's password:

root@fso2025:~# ssh 192.168.3.10
root@192.168.3.10's password:

root@fso2025:~# ssh 192.168.4.10
root@192.168.4.10's password:

root@fso2025:~# ssh 192.168.12.10
kex_exchange_identification: read: Connection reset by peer
Connection reset by 192.168.12.10 port 22
root@fso2025:~# ssh 192.168.13.10
kex_exchange_identification: read: Connection reset by peer
Connection reset by 192.168.13.10 port 22
root@fso2025:~# ssh 192.168.14.10
kex_exchange_identification: read: Connection reset by peer
Connection reset by 192.168.14.10 port 22
root@fso2025:~# █
```

5. En MAQUINA1 habilita los servicios telnet añadiendo la siguiente línea a /etc/inetd.conf

```
telnet      stream    tcp nowait root /usr/sbin/tcpd  telnetd
```

From:

<https://knoppia.net/> - **Knoppia**

Permanent link:

https://knoppia.net/doku.php?id=master_cs:fortificacion:p5&rev=1741706073

Last update: **2025/03/11 15:14**

